## CONTINUOUS BAND SEALING OF MEDIUM TO HEAVY DUTY APPLICATIONS FOR DIFFICULT TO SEAL POUCH / BAG MATERIALS

# **MODEL VBS-DH-10**

- USDA Approved rotary sealing system.
- Unit is designed with two 5" heating sections (10" total) and two 5" cooling sections (10" total) for greater flexibility in product sealing of difficult materials with temperatures up to 500 degrees +/- 2 degrees Fahrenheit.
- Extra sealing capacity allows speeds up to 45' per minute with constant secure seals of 1/8", 1/4" or 3/8" wide without bag top trimmer.
- Designed to seal Kraft/PE, Nylon, Polyethylene, 

   Polypropylene, Laminates, Tyvek / Polymylar and Foil.
- Seals are achieved through the use of special heavy duty wear-resistant laminated Teflon bands.





- Dual temperature controls maintain consistent heat and assures quality hermetic seals. Heat is generated from front and rear heaters or one set only as required using a simple on/off switch. Individual heating assemblies can be regulated because of dual controls.
- Mounted on a heavy duty floor model adjustable stand with crank handle and can be operated in the vertical or horizontal position. Unit can be positioned over existing lower carry conveyor.
- Chassis sealing assembly construction of stainless steel shafting throughout and anodized aluminum assuring longevity of use. Chrome plated sealing assemblies reduces wear.
- Adjustable height sealing assembly with crank handle.
- No compressed air required, 110V, 1 Phase, 60 Cycle.

### **APPLICATIONS**

Medical Pharmaceutical Chemicals Food Candy Textiles Poultry Meat Bakery Toys

#### Seafood Crafts Disposables Hardware

Garden

Electronics Pet Decorative Automotive Mailroom

OVER 50 YEARS OF SUCCESSFUL PACKAGING EXPERIENCE

## ALL PACKAGING MACHINERY, CORP.

90 13th Avenue, Ronkonkoma, NY 11779 (631) 588-7310 Fax (631) 467-4690 Call Toll Free 1-800-637-8808 www.allpackagingmachinery.com



